# Wallacia Wastewater Treatment Plant June Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-06-2022 to 30-06-2022 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 05-07-2022 Date published: 15-07-2022

### Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	<2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	-	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	3.4	
faecal coliforms	CFU/100mL	every 6 days	5	<1	<1	1	
hydrogen sulphide (unionised)	ug/L	monthly	1	_	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.07	0.13	0.19	
nitrogen (total)	mg/L	every 6 days	5	4.26	4.83	5.55	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.04	0.05	0.07	
total suspended solids	mg/L	every 6 days	5	<2	<2	<2	
zinc	ug/L	monthly	1	-	_	13	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant May Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-05-2022 to 31-05-2022 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 06-06-2022 Date published: 17-06-2022

### Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	3	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	_	_	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	2.9	
faecal coliforms	CFU/100mL	every 6 days	5	<1	3	8	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	-	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.03	0.11	0.22	
nitrogen (total)	mg/L	every 6 days	5	3.33	4.35	5.32	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.03	0.04	0.04	
total suspended solids	mg/L	every 6 days	5	<2	<2	4	
zinc	ug/L	monthly	1	_	_	12	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant April Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-04-2022 to 30-04-2022 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 09-05-2022 Date published: 20-05-2022

### Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	<2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	-	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	3.4	
faecal coliforms	CFU/100mL	every 6 days	5	<1	5	14	
hydrogen sulphide (unionised)	ug/L	monthly	1	_	-	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.01	0.14	0.6	
nitrogen (total)	mg/L	every 6 days	5	2.44	3.32	4.14	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.04	0.05	0.1	
total suspended solids	mg/L	every 6 days	5	<2	<2	<2	
zinc	ug/L	monthly	1	-	_	13	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant March Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-03-2022 to 31-03-2022 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 05-04-2022 Date published: 15-04-2022

Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank							
pollutant	unit of measure	3DGM limit   3DGM Actual   within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes			
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes			
total suspended solids	mg/L	monthly	10	<2	yes			

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	_	_	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	3	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	6.1	
faecal coliforms	CFU/100mL	every 6 days	5	<1	1	3	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.03	1.34	4.05	
nitrogen (total)	mg/L	every 6 days	5	2.76	3.69	5.55	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.05	0.14	0.32	
total suspended solids	mg/L	every 6 days	5	<2	3	8	
zinc	ug/L	monthly	1	_	-	11	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant February Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-02-2022 to 28-02-2022 Licensee: Sydney Water Corporation

PO Box 399

Date published: 24-03-2022 PARRAMATTA NSW 2124

### Table 1: 3 Day Geometric Mean data

Date obtained: 15-03-2022

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank							
pollutant	unit of measure	3DGM limit   3DGM Actual   within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes			
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes			
total suspended solids	mg/L	monthly	10	<2	yes			

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	_	_	7	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	3.1	
faecal coliforms	CFU/100mL	every 6 days	5	<1	2	5	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	-	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.01	0.32	1.54	
nitrogen (total)	mg/L	every 6 days	5	2.91	4.11	4.68	
nonylphenol ethoxylate	ug/L	monthly	1	-	_	<5	
phosphorus (total)	mg/L	every 6 days	5	0.04	0.11	0.35	
total suspended solids	mg/L	every 6 days	5	<2	<2	8	
zinc	ug/L	monthly	1	_	_	12	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant January Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-01-2022 to 31-01-2022 Licensee: Sydney Water Corporation

Date obtained: 08-02-2022 PO Box 399

Date published: 11-02-2022 PARRAMATTA NSW 2124

### Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank							
pollutant	unit of measure	3DGM limit   3DGM Actual   within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes			
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes			
total suspended solids	mg/L	monthly	10	3	yes			

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	-	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	-	14.4	
copper	ug/L	monthly	1	-	-	1.2	
faecal coliforms	CFU/100mL	every 6 days	5	<1	4	11	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	-	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.01	0.1	0.4	
nitrogen (total)	mg/L	every 6 days	5	2.92	3.7	4.31	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.05	0.08	0.13	
total suspended solids	mg/L	every 6 days	5	<2	<2	2	
zinc	ug/L	monthly	1	-	_	<1	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant December Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-12-2021 to 31-12-2021 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 07-01-2022 Date published: 20-01-2022

Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank  unit of sampling frequency 3DGM limit 3DGM Actual within limits					
pollutant						
biochemical oxygen demand	mg/L	monthly	25	<2	yes	
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes	
total suspended solids	mg/L	monthly	10	<2	yes	

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	_	_	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	4.6	
faecal coliforms	CFU/100mL	every 6 days	5	<1	7	14	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.02	0.15	0.66	
nitrogen (total)	mg/L	every 6 days	5	2.65	3.98	4.61	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.06	0.14	0.24	
total suspended solids	mg/L	every 6 days	5	<2	<2	3	
zinc	ug/L	monthly	1	_	_	15	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant November Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-11-2021 to 30-11-2021 Licensee: Sydney Water Corporation

PO Box 399

Date published: 17-12-2021 PARRAMATTA NSW 2124

### Table 1: 3 Day Geometric Mean data

Date obtained: 07-12-2021

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling sampling and some sampling sampling sampling specified sampling sampling specified sampling sa						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	<2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	-	5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	13.7	
faecal coliforms	CFU/100mL	every 6 days	5	<1	1	2	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.05	0.21	0.68	
nitrogen (total)	mg/L	every 6 days	5	2.12	3.02	3.71	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.04	0.07	0.1	
total suspended solids	mg/L	every 6 days	5	<2	<2	<2	
zinc	ug/L	monthly	1	-	_	16	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant October Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-10-2021 to 31-10-2021 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 08-11-2021 Date published: 12-11-2021

Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limits						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	-	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	11.6	
faecal coliforms	CFU/100mL	every 6 days	5	<1	7	30	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.02	0.04	0.09	
nitrogen (total)	mg/L	every 6 days	5	3.2	3.63	4.33	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.07	0.07	0.08	
total suspended solids	mg/L	every 6 days	5	<2	<2	3	
zinc	ug/L	monthly	1	-	_	16	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

### Wallacia Wastewater Treatment Plant September Pollution Monitoring Summary



### **EPL 12235**

Date obtained: 07-10-2021

Summary period: 01-09-2021 to 30-09-2021 Licensee: Sydney Water Corporation

PO Box 399

Date published: 13-10-2021 PARRAMATTA NSW 2124

Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	<2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	_	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	_	_	3.3	
faecal coliforms	CFU/100mL	every 6 days	5	<1	<1	1	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.01	0.06	0.15	
nitrogen (total)	mg/L	every 6 days	5	3.38	4.9	6.61	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.07	0.08	0.11	
total suspended solids	mg/L	every 6 days	5	<2	<2	<2	
zinc	ug/L	monthly	1	_	_	17	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant August Pollution Monitoring Summary



### **EPL 12235**

Summary period: 01-08-2021 to 31-08-2021 Licensee: Sydney Water Corporation

PO Box 399

PARRAMATTA NSW 2124

Date obtained: 07-09-2021 Date published: 13-09-2021

### Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	25	<2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	-	_	<5	
biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	3	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	_	_	4.9	
faecal coliforms	CFU/100mL	every 6 days	6	<1	<1	2	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	5	0.02	0.19	0.79	
nitrogen (total)	mg/L	every 6 days	5	4.11	4.8	5.59	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	5	0.05	0.05	0.07	
total suspended solids	mg/L	every 6 days	5	<2	<2	<2	
zinc	ug/L	monthly	1	_	_	24	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

# Wallacia Wastewater Treatment Plant July Pollution Monitoring Summary



### **EPL 12235**

Date obtained: 09-08-2021

Summary period: 01-07-2021 to 31-07-2021 Licensee: Sydney Water Corporation

PO Box 399

Date published: 18-08-2021 PARRAMATTA NSW 2124

#### Table 1: 3 Day Geometric Mean data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of sampling measure frequency 3DGM limit 3DGM Actual within limit						
biochemical oxygen demand	mg/L	monthly	25	<2	yes		
carbonaceous biochemical oxygen demand	mg/L	monthly	25	<2	yes		
total suspended solids	mg/L	monthly	10	<2	yes		

<sup>3</sup> Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 4 Site code WL0004	Point description: From the dechlorination tank						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	_	_	<5	
biochemical oxygen demand	mg/L	every 6 days	6	<2	<2	<2	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	6	<2	<2	<2	
Ceriodaphnia dubia immobilisation (EC50)	% Effluent/Vol	monthly	1	-	_	100	
copper	ug/L	monthly	1	-	_	20.9	
faecal coliforms	CFU/100mL	every 6 days	5	<1	<1	<1	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
nitrogen (ammonia)	mg/L	every 6 days	6	0.18	0.4	0.77	
nitrogen (total)	mg/L	every 6 days	6	5.1	5.8	6.67	
nonylphenol ethoxylate	ug/L	monthly	1	-	-	<5	
phosphorus (total)	mg/L	every 6 days	6	0.04	0.05	0.06	
total suspended solids	mg/L	every 6 days	6	<2	<2	2	
zinc	ug/L	monthly	1	_	_	19	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.